HQ 1500



WATER & ICE COUNTERTOP PURIFICATION SYSTEM




Innovative Design & Technology

- SafeTouch™ surface with silver ion antimicrobial technology
- Combination ice maker & water dispenser
- Dispenses chewable ice, as well as hot and room temperature water
- TDS management technology featuring the ability to flush the evaporator.



Advanced Hygiene Features

- LED UV keeps the water reservoir clean
- Advanced purification system
- Touch-activated sensor operation for easy cleaning



Bullet-Proof Reliability

- Available with optional base cabinet to make free-standing
- Only 17.5" high fits under most cabinet









Hydrate HQ of Georgia 5238 Royal Woods Parkway Tucker, GA 30084 770.430.3400 Hydrate HQ of Mid Atlantic 1550 Caton Center Dr. Ste. D Baltimore, MD 21227 443.873.0300

Hydrate HQ of SoCal Hydrate HQ of San Diego 9340 Santa Anita Ave. Ste. 103 Rancho Cucamonga, CA 91730 909.454.3400



HQ 1500 COUNTERTOP WATER & ICE PURIFICATION SYSTEM



- High-capacity ice production to meet most office needs
- Touch-activated sensor operation for easy cleaning
- Safety button for hot water dispensing
- Hot and ambient water

- LED UV to help maintain water reservoir cleanliness
- Produces chewable ice
- 7 lbs of ice storage capacity
- Produces 125 lbs of ice per day

Freestanding

Weight	103.9 lbs (47.1 kgs)
Dimensions	45" h x 14.1" w x 21.7" d (114.3 h x 35.814 w x 55.118 d)
Ambient Capacity	Tankless
Hot Tank Capacity	0.33 gallons (1.25 liters)
Ice Storage Capacity	7 lbs. (3.2 kg)
Ice Amount Per Day	125 lbs (56.7 kg)
Dispensing Height	9" (21.9 cm)
Power Consumption	2.83 kWh/24 hours
Rated Voltage/Frequency	120V and 230V 50/60hz
Power Consumption	1.6kWh / 24 hours

Countertop

Weight	71.9 lbs (32.6 kgs)
Dimensions	17.7" h x 14.1" w x 21.7" d (44.958 h x 35.814 w x 55.118 d)
Ambient Capacity	Tankless
Hot Tank Capacity	0.33 gallons (1.25 liters)
Ice Storage Capacity	7 lbs. (3.2 kg)
Ice Amount Per Day	125 lbs (56.7 kg)
Dispensing Height	9" (22.9 cm)
Power Consumption	2.83 kWh/24 hours
Rated Voltage/Frequency	120V and 230V 50/60hz
Power Consumption	1.05 kWh / 24 hours



Hydrate HQ of Georgia 5238 Royal Woods Parkway Tucker, GA 30084 770.430.3400 Hydrate HQ of SoCal Hydrate HQ of San Diego 9340 Santa Anita Ave. Ste. 103 Rancho Cucamonga, CA 91730 909.454.3400

Certified by IAPMO in accordance with ANSI/NSF 372 for lead free products and certified by IAPMO R&T in accordance with UL 399 and CSA 22.2 for electrical safety. U.S. Pat. No. 11,946,682 BI